


Switch - HZ-1008POE



6FE POE+2FE UPLINK POE Switch

3. Características

Produto	6+2 10/100Mbps Port POE Switch
Modelo	HZ-1008POE
Porta POE	1 to 6 support IEEE802.3AF/AT Standard
Potência de saída	15.4W/30W IEEE802.3af/at
Pino de alimentação	Both 1/2+, 3/6- and 4/5+7/8-
Poder total	≤78W (52V 1.5A)
Protocolo POE	IEEE 802.3af/IEEE 802.3at
Tipo POE	End-span
Distância de transmissão	≤250m
Padrão de rede	IEEE 802.3, IEEE802.3u, 802.3x
Meio de rede	10/100BASE-TX:5 class and above non shielded twisted pair
Capacidade de troca	1.6Gbps
Modo de encaminhamento	Store and forward
Taxa de encaminhamento	10BASE-T: 14880pps/port 100BASE-tx: 148800pps/port
Endereço MAC	MAC address table 1K
Função de Porta	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Indicador LED	LINK/ACT.100Mbps;POE Status Indicator; Power indicator; Extender
Indicador de trabalho	Working temperature : -10°-- 55°C
Peso	1kg
Tamanho	200mm*118mm*44mm(L*W*H)